

ISO 9001:2008 Registered

Digital Hanging & Crane Scales

CS200™ Hanging Scale / CS750™ Hanging Scales / CS1500™ Crane Scales / CS3000™ Crane Scales



Intercomp[®]
advanced weighing technology . . . by any measure

intercompcompany.com

Digital Hanging & Crane Scales

CS200™

High Accuracy, Compact Digital Hanging Scales for Low Capacity Applications

Available in 25lb (13kg) to 500lb (250kg) Capacities, this extremely compact and light-weight scale weighs only 1.6 lb (0.7kg). Features a large, easy-to-read, 0.5" Backlit LCD Display, large push button controls and operates up to 300 hours on a standard 9-Volt Battery.



Part Number	Capacity	Graduation
100775	25lb (13kg)	.01lb (.01kg)
100774	50lb (25kg)	.02lb (.01kg)
100773	100lb (50kg)	.05lb (.02kg)
100772	250lb (125kg)	.1lb (.05kg)
100771	500lb (250kg)	.2lb (.1kg)

Includes:

- Top Eye Hook
- Bottom Hook

Performance

Accuracy: ±0.1%

Controls

General: On/Off, Zero & lb/kg
Display: 0.5" (12mm) LCD

Environmental

Humidity: 10 to 95% Non-Condensing
Temperature: -4° to 140°F (-20° to 60°C)

Physical

Overload: 200% of Capacity

Electrical

Battery: Standard Alkaline or Rechargeable 9-Volt
Battery Life: 300 Hours

CS750™

NTEP Approved Models Available

Heavy Duty Digital Hanging Scale for Light Industrial Applications

This heavy-duty hanging scale features a large, easy-to-read, 1" Backlit LCD Display, large push button controls and operates up to 250 hours on standard D-Cell Batteries.



Infrared Remote Control Standard

Part Number	Capacity	Graduation
100652	100lb (50kg)	.05lb (.02kg)
100653	300lb (150kg) *	.10lb (.05kg)
100654	500lb (250kg) *	.2lb (.1kg)
100655	1,000lb (500kg) *	.5lb (.2kg)

* NTEP approved

Includes

- Infrared Remote Control
- Crosby Eye Hook
- Bottom Swivel Hook

Performance

Accuracy: ±0.1%

Controls

General: On, Off, Zero & Backlight
Display: 1" (25mm) LCD
Indicators: lb/kg

Environmental

Humidity: 10 to 95% Non-Condensing
Temperature: -4° to 140°F (-20° to 60°C)

Physical

Overload: 200% of Capacity

Electrical

Battery: Standard Alkaline or Rechargeable D-Cell
Battery Life: 250 Hours

Options:

- RS232 Serial Output
- LED Display
- Direct Power
- Printer

CS1500™ NTEP Approved for All Capacities

Low-cost, High Performance Digital Crane Scale for Medium Capacity Industrial Applications

The CS1500- Crane scale features a large, easy-to-read, LED Display, large push button controls and operates up to 300 hours on standard D-Cell Batteries.



Infrared
Remote
Control



Part Number	Capacity	Graduation
100661	500lb (250kg) *	.2lb (.1kg)
100662	1,000lb (500kg) *	.5lb (.02kg)
100663	2,000lb (1,000kg) *	1lb (1kg)
100664	5,000lb (5,000kg) *	2lb (1kg)
100665	10,000lb (5,000kg) *	5lb (2kg)
100666	20,000lb (10,000kg) *	10lb (5kg)

* NTEP approved

Includes:

- Infrared Remote Control
- Crosby Eye Hook
- Bottom Swivel Hook

Performance

Accuracy: ±0.1%

Controls

General: On, Off, Zero, Tare, Print, Mode & Set
Display: 0.8" (20mm) LED
Indicators: lb/kg, Gross, Net, Tare & Peak Hold

Environmental

Humidity: 10 to 95% Non-Condensing
Temperature: -4° to 140°F (-20° to 60°C)

Physical

Overload: 200% of Capacity

Electrical

Battery: Standard Alkaline or Rechargeable D-Cell
Battery Life: 30 Hours

Options:

RS232 Serial Output
LCD Display
Direct Power
Printer

CS3000™ NTEP Approved Models Available

Fully Featured High Capacity Industrial Crane Scale for Heavy Duty Applications

The CS3000- now features Fully Integrated RFX™ Wireless Weighing Technology. The Handheld RFX™ Wireless Indicator controls scale functions at a safe distance, including On and Off, improving any operation.



Part Number	Capacity	Graduation
100681-RFX	2,000lb (1,000kg) *	1lb (1kg)
100682-RFX	5,000lb (5,000kg) *	1lb (1kg)
100683-RFX	10,000lb (5,000kg) *	2lb (1kg)
100684-RFX	20,000lb (10,000kg) *	5lb (2kg)
100685-RFX	30,000lb (15,000kg) *	10lb (5kg)
100686-RFX	50,000lb (25,000kg) *	10lb (5kg)
100687-RFX	70,000lb (35,000kg)	20lb (10kg)
100688-RFX	100,000lb (50,000kg)	20lb (10kg)

Larger Capacities Available Upon Request
* NTEP approved

Includes:

- Handheld RFX™ Wireless Indicator with Rechargeable Batteries, Battery Charger & Case
- Top Eye Hook
- Crosby S-1 Swivel Hook

Performance

Accuracy: ±0.1%

Controls

General: Power, Accum Total, Mode, Zero, lb/kg, Tare
Display: 2" (51mm) LCD
Indicators: lb, kg, Net, Gross, Total, Tare, S1, S2, Peak, Battery Life

Environmental

Humidity: 10 to 95% Non-Condensing
Temperature: -4° to 140°F (-20° to 60°C)

Physical

Overload: 200% of Capacity

Electrical


Battery in Scales: Standard Alkaline or Rechargeable D-Cell
Battery Life in Scales: 3,000 Hours
Battery in Indicator: Standard Alkaline or Rechargeable AA
Battery Life in Indicator: 40 Hours

Options:

RS232 Serial Output
Direct Power
Printer
Anti-Heat Shield (Foundry Package)
Anti-Magnetic Shield
Oversized Top Eye Hook or Shackle

3,000 Hour Battery
Life in Scales
40 Hours in Indicator





Intercomp Company, Inc. is the world's largest manufacturer of portable weighing solutions, and has been serving the industrial, material handling and transportation industries for over 30 years. With ISO 9001:2008 Registered facilities in the United States and United Kingdom and all standards traceable to NIST, we can deliver the products to meet your most exacting specifications.

See for yourself how Intercomp provides advanced weighing technology...by any measure.

CE ISO 9001:2008
Registered




Made In U.S.A.

intercompcompany.com

Toll Free: 800-328-3336

Worldwide: 763/476-2531 • Fax: 763/476-2613

Email: info@intercompcompany.com

Intercomp[®]
advanced weighing technology ... by any measure

3839 County Road 116
Medina, Minnesota 55340-9342 U.S.A.